

**REMARKS**

By way of the foregoing amendments, Claims 1-11 have been amended and new claims 12-20 are presented for consideration. The new claims are presented to conform to the claims presented during the international phase, with additional changes in claim wording intended solely to place the claims in a form more closely corresponding to U.S. practice. Also a new Abstract is submitted. No new matter has been introduced by these changes.

In addition, submitted with this Preliminary Amendment is a substitute specification. The substitute specification sets forth proper headings according to typical U.S. practice. No new matter has been introduced.

Early and favorable consideration with respect to the application is respectfully requested.

Should any questions arise in connection with this application, the undersigned respectfully requests that he be contacted at the number indicated below.

Respectfully submitted,

BUCHANAN INGERSOLL and ROONEY PC

Date: September 25, 2006

By: Matthew L. Schneider  
Matthew L. Schneider  
Registration No. 32814

P.O. Box 1404  
Alexandria, Virginia 22313-1404  
(703) 836-6620

=1-

Description

**Railway bogie**

**RAILWAY BOGIE**

**FIELD OF THE INVENTION**

[0001]\_\_The invention relates to a railway bogie comprising at least one hydraulic spring having a housing being required for a functionality of said ~~the~~ hydraulic spring and an axlebox.

**BACKGROUND DISCUSSION**

[0002]\_\_From UIC standard a bogie with helical springs is well known, whereby the axlebox suspension consists of helical springs in combination with friction damping. Thereby the springs rest on support arms integral with the lower part of the axlebox housing and are connected with the bogie frame using caps integral with the bogie frame for taking up the top of the springs.

[0003]\_\_US 2002-0089-102 A1 discloses a hydraulic spring comprising a membrane. ~~Therein it is~~ This document also discloses ~~discloses~~ that said ~~the~~ hydraulic spring is for use in rail vehicles especially as a primary spring.

[0004]\_\_Further the catalogue of the company ContiTech Luftfedersysteme GmbH in Hannover, Germany, "Air Spring Systems for Modern Rail Vehicles", printed and distributed in October 1998 discloses the use of hydraulic springs comprising a membrane in two-axle bogies.

[0005]\_\_One object of the present invention is to provide an improved railway bogie comprising at least an axlebox and a hydraulic spring, so that the railway bogie has a simplified build-up and is therewith cheaper to produce.

~~The object of the invention is achieved by the subject of claim 1. Preferable embodiments are described in the dependent claims.~~

### SUMMARY

[0006]\_\_According to ~~claim 1~~one aspect, a railway bogie ~~comprising~~comprises at least one hydraulic spring having a housing ~~being required for a~~operativeness of said ~~the~~ hydraulic spring and an axlebox ~~is characterized by the fact that, wherein~~ at least a part of said ~~the~~ axlebox forms at least a part of said ~~the~~ housing.

[0007]\_\_By the fact that an ~~anyway~~-existing part of the axlebox is designed and used to form a part of the housing of the hydraulic spring, the number of components is reduced in total so that a lower fault liability and a more ~~favourable~~favorable cost position can be achieved.

### BRIEF DESCRIPTION OF THE DRAWING FIGURES

[0008]\_\_Further advantages, features and details of the invention are described with respect to one preferred embodiment of the invention with reference to the accompany drawings ~~wherein~~.

[0009]\_\_Figure 1 is a longitudinal cross section in the region of one wheel of a bogie ~~and~~.

[0010]\_\_Figure 2 is a sectional view along the line B-B of Figure 1.

### DETAILED DESCRIPTION

[0011]\_\_Figure 1 shows a longitudinal cross section in the region of one wheel 2 of a bogie of the so-called Y 25 type, whereby the cut is directed ~~according to~~along a plane ~~being~~ defined by the axes of rotational symmetry of a first and second

hydraulic spring. The pictured section of the bogie comprises an axlebox 10 with a rolling bearing 4 mounted in a middle region of the axlebox 10. The rolling bearing 4 supports one end of one of the two axles of the bogie.

[0012] A base of the axlebox 10 is extended to the left and the right side forming a cup shaped region 12 at each of ~~said the~~ sides. Each of ~~said the~~ hydraulic springs comprises a spring element 20, which is attached to each of ~~said the~~ cup shaped regions 12 of the axlebox 10. A metallic ~~entrepièces~~centerpieces 26 is located in the centre of each of the spring elements 20.

[0013] These two ~~entrepièces~~centerpieces 26 are attached to one bridging adapter 50. Therefore the ~~entrepièces~~centerpieces 26 and the bridging adapter 50 have bores for connecting the ~~entrepièces~~centerpieces 26 with the bridging adapter 50 via two bolts 52 pictured uncut in Figure 1 and 2. In other embodiments, the bolts 52 can be integral parts of the ~~entrepièces~~centerpieces 26 or of the bridging adapter 50, or the ~~entrepièces~~centerpieces 26 can be connected to the bridging adapter 50 by any other connecting means.

[0014] The bridging adapter 50 is attached to a longeron of a frame 6 of the bogie, ~~whereby this.~~ This longeron extends in a longitudinal direction parallel to the rails and is pictured uncut in Figure 1. Preferably the bridging adapter 50 is connected to the bogie frame 6 by welding.

[0015] In the following description, just ~~that the~~ left cup shaped region 12 in connection with the left spring element 20 is described in detail, because the same applies to the right cup shaped region 12 in connection with the right spring element 20. Therefore Figure 2 shows a sectional view along the line B-B of Figure 1. The spring element 20 comprises sleeve shaped elastomeric elements 22 and intermediate sleeve shaped metallic elements 24 in an alternating succession, whereby the elastomeric and the metallic elements 22 and 24 are connected by way of ~~vulcanisation~~vulcanization. Also the ~~entrepièces~~centerpieces 26 is connected by way of ~~vulcanisation~~vulcanization to its adjacent elastomeric element 22.

[0016]\_\_The spring element 20 is secured to the respective cup shaped region 12 of the axlebox 10 via a sealing ring 42, which is attached to the axlebox 10 via screws 44. In other embodiments the spring element 20 also can be directly ~~vulcanised~~vulcanized to the cup shaped region 12. The spring elements 20 forms together with the respective cup shaped region 12 of the axlebox 10 a volume for a fluid 30 particularly a hydraulic fluid. This volume is at least partly filled with the fluid 30. ~~The centrepiece~~ The centerpiece 26 is prolonged into ~~said the~~ volume forming a plunger shaped region 28. Thereby at least a disk shaped region at the end of the plunger shaped region 28 is dipped into the fluid 30, so that this arrangement fulfils the function of a damper. ~~So the~~ The cup shaped region 12 of the axlebox 10 together with the respective spring element 20 and the fluid 30 form together the hydraulic spring.

[0017]\_\_In another embodiment of the invention, a hydraulic spring can be used, e.g. according to the already cited US 2002-0089102 A1, comprising a membrane instead of the plunger shaped section 28 of the ~~centrepiece~~centerpiece 26, whereby the cup shaped region 12 of the axlebox 10 is then also one part of the housing of the hydraulic spring.

List of reference signs

2 — wheel

4 — rolling bearing

6 — bogie frame

10 —

ABSTRACT OF THE DISCLOSURE

An axlebox

12 — cup-shaped region

20 — spring element

22 — elastomeric element

24 — metallic element

26 — centrepiece

28 — plunger-shaped region

30 — fluid

42 — sealing ring

44 — screw

50 — bridging adapter

52 — bolt

--unit of a railway bogie includes at least one hydraulic spring having a housing required for functionality of the hydraulic spring, and an axlebox, At least a part of the axlebox forms at least a part of the housing